

TECHNICAL DATA SHEET

Name

TIARA

Code

45090E S3 SRC ESD

Product Range



Standard

S3 SRC ESD

EN ISO

20345:2011

Weight

600 grams
(1 shoe in size 42)

Size range

35 <-> 48

Mondopoint

11

Packaging

10 pairs/carton
(same size)

TECHNICAL SPECIFICATIONS



BEST SELLER

SOLE

SOLE FEATURES



THERMO GRIP® soles feature a PU foam midsole and a thermo-polyurethane outsole, designed for superior grip, even weight distribution, thermal insulation, and anti-abrasion reinforcement.

PROTECTIVE ELEMENTS

UPPER

LINING

FOOTBED



Multilayer polymeric toe cap, approximately 40% lighter than steel, yet able to resist impacts of up to 200 Joules and compressive loads of up to 15 Kilonewtons. Non-magnetic, thermally insulating, and corrosion-resistant, it provides complete protection for the toes.

Crafted from multilayer polyester fabric, this protective plate is around 40% lighter than steel while delivering the same resistance to penetration forces, up to 1,100 Newtons. Flexible, non-magnetic, thermally insulating, corrosion-resistant and hypoallergenic, it safeguards 100% of the foot's resting surface.

High-quality nubuck leather with a fine finish for a smooth, premium surface. Treated to resist stains and abrasion, while preserving breathability and softness for lasting comfort.

Three-layer mesh ensuring breathability, moisture control, and lasting comfort.

Removable polyurethane insole with integrated gel for superior impact absorption. Incorporates ESD technology to safely dissipate electrostatic charges.

EXTRA



SAFETY TECHNICAL SPECIFICATIONS

Description	Measurement Unit	Requirement	Test Result
TOE CAP: Impact resistance	mm	≥ 14	16,5
TOE CAP: Compression resistance	mm	≥ 14	15,5
ANTI-PUNCTURE PLATE: Penetration resistance	N	≥ 1.100	pass
FOOTWEAR: Antistatic properties (in wet condition)	MΩ	≥ 0,1	19,9
FOOTWEAR: Antistatic properties (in dry condition)	MΩ	≤ 1.000	328
UPPER: Water vapour permeability	mg/cm2*h	≥ 0,8	4,4
UPPER: Water vapour coefficient	mg/cm2	≥ 15	43,6
UPPER: Water penetration after 60 min	g	≤ 0,2	0,2
UPPER: Water absorption after 60 min	%	≤ 30	12,9
INTERNAL LINING: Water vapour permeability	mg/(cm2*h)	≥ 2,0	35,5
INTERNAL LINING: Water vapour coefficient	mg/cm2	≥ 20	284,1
OUTSOLE: Abrasion resistance	mm3	≤ 150	38
OUTSOLE: Energy absorption of seat region (E)	J	≥ 20	34
OUTSOLE: Flexural resistance	mm	≤ 4	0
OUTSOLE: Interlayer bond strength	N/mm	≥ 4	5,8
OUTSOLE: Resistance to fuel oil (FO)	%	≤ 12	0,7

ADDITIONAL FEATURES

Test	Measurement Unit	Requirement	Results
Electrical resistance for ESD footwear <small>Requirements IEC 61340-5-1:2016</small>	MΩ	≤ 100	92,1
Resistance to hot contact (HRO)	-	autosoles shall not melt and develop any cracks when bent	-
Cold insulation of outsole complex (CI) 30min/-17°C <small>(temperature decrease on the upper surface of the insock)</small>	°C	≤ 10	-
Heat insulation of outsole complex (HI) 30min/150°C	°C	≤ 22	-
Water resistance (WR) <small>(Total wetted area inside the footwear)</small>	cm2	after 80 min.	-
Electric hazard resistance (EH) 18kV / 60 Hz <small>(Electric flux)</small>	MΩ	≤ 100	-

STORAGE, CARE AND MAINTENANCE

- PANDA SAFETY footwear should be stored in original packaging, storage temperature should not exceed 35°C, humidity should be less than 80% and without the influence of direct sunlight.
- Sandals, shoes and boots should be cleaned after each use; dry off the shoes, not in proximity to or in direct contact with stoves or other sources of heat.
- Carry out the periodic treatment of the uppers with suitable products containing wax, grease, silicone, etc.
- Avoid contact with aggressive chemicals and extreme temperatures.
- Verify the good state before each use.

SOLE DESIGN AND PERFORMANCE



ENERGY ABSORPTION COEFFICIENT IN THE HEEL AREA



INDUSTRIES

