

TECHNICAL DATA SHEET

SAFETY

PANDA®

Italian Style at Work

Name

REGATA

Product Range

Standard
TOP CLASSIC

Code

LX-2519 S3L FO SR

EN ISO

20345:2022+A1:2024

Weight

590 grams
(1 shoe in size 42)

Size range

36 < 48

11

Mondopoint
6 pairs/carton
(same size)

Packaging

TECHNICAL SPECIFICATIONS



BEST SELLER

SOLE

SOLE FEATURES



The LX® sole offers anti-static properties, anti-torsion support, and top-level slip resistance. Its PU foam midsole ensures all-day comfort, while the thermo-polyurethane tread delivers excellent grip, thermal insulation, and a self-cleaning effect.

ANATOMICAL INTERNAL PROFILE

self cleaning

ANTI TORSION

ARCH SUPPORT

PROTECTIVE ELEMENTS

UPPER

LINING

FOOTBED



Multilayer polymeric toe cap, approximately 40% lighter than steel, yet able to resist impacts of up to 200 Joules and compressive loads of up to 15 Kilonewtons. Non-magnetic, thermally insulating, and corrosion-resistant, it provides complete protection for the toes.



Crafted from multilayer polyester fabric, this protective plate is around 40% lighter than steel while delivering the same resistance to penetration forces, up to 1,100 Newtons. Flexible, non-magnetic, thermally insulating, corrosion-resistant, and hypoallergenic, it safeguards 100% of the foot's resting surface.



Waterproof leather treated to protect against moisture without reducing breathability. Ensures durability and abrasion resistance in environments exposed to liquids.



Three-layer mesh ensuring breathability, moisture control, and lasting comfort.



Removable insole that evenly distributes weight, adapts to foot morphology, and provides anti-static, antibacterial, antifungal, and ESD protection. A cushioned heel insert further enhances comfort.

EXTRA



SAFETY TECHNICAL SPECIFICATIONS

Description	Measurement Unit	Requirement	Test Result
TOE CAP: Impact resistance	mm	≥ 14	18
TOE CAP: Compression resistance	mm	≥ 14	20,5
ANTI-PUNCTURE PLATE: Penetration resistance	N	≥ 1.100	pass
FOOTWEAR: Antistatic properties (in wet condition)	MΩ	≥ 0,1	10
FOOTWEAR: Antistatic properties (in dry condition)	MΩ	≤ 1.000	380
UPPER: Water vapour permeability	mg/cm ² *h	≥ 0,8	1,5
UPPER: Water vapour coefficient	mg/cm ²	≥ 15	19,2
UPPER: Water penetration after 60 min	g	≤ 0,2	0
UPPER: Water absorption after 60 min	%	≤ 30	2,2
INTERNAL LINING: Water vapour permeability	mg/(cm ² *h)	≥ 2,0	39,7
INTERNAL LINING: Water vapour coefficient	mg/cm ²	≥ 20	317,7
OUTSOLE: Abrasion resistance	mm ³	≤ 150	68
OUTSOLE: Energy absorption of seat region (E)	J	≥ 20	44
OUTSOLE: Flexural resistance	mm	≤ 4	3,5
OUTSOLE: Interlayer bond strength	N/mm	≥ 4	12,4
OUTSOLE: Resistance to fuel oil (FO)	%	≤ 12	2,2

SOLE DESIGN AND PERFORMANCE



TRACTION STABILITY GRIP BRAKING SELF-CLEANING LADDER GRIP

0 MINIMUM VALUE REQUIRED 20 TEST RESULT 44 120% ENERGY ABSORPTION COEFFICIENT IN THE HEEL AREA

INDUSTRIES



ADDITIONAL FEATURES

	Measurement Unit	Requirement	Results
Electrical resistance for ESD footwear	MΩ	≤ 1,00	-
Resistance to hot contact (HRO)	-	autosoles shall not melt and develop any cracks when bent	-
Cold insulation of outsole complex (CI) 30min/-17°C (temperature decrease on the upper surface of the insole)	°C	≤ 10	-
Heat insulation of outsole complex (HI) 30min/150°C	°C	≤ 22	-
Water resistance (WR)	cm ²	after 80 min.	-
Electric hazard resistance (EH) 18kV / 60 Hz (Electric flux)	MΩ	≤ 100	-

STORAGE, CARE AND MAINTENANCE

- PANDA SAFETY footwear should be stored in original packaging, storage temperature should not exceed 35°C, humidity should be less than 80% and without the influence of direct sunlight.
- Sandals, shoes and boots should be cleaned after each use; dry off the shoes, not in proximity to or in direct contact with stoves or other sources of heat.
- Carry out the periodic treatment of the uppers with suitable products containing wax, grease, silicone, etc.
- Avoid contact with aggressive chemicals and extreme temperatures.
- Verify the good state before each use.