

BLACK ROCK

222BB-01 S3S SC FO LG SR

STANDARD EN ISO 20345:2022+A1:2024

SIZES 37-47

Maximum stability and durability thanks to the **TPU** protection element applied to the rear of the footwear to provide increased protection against impacts, friction, and to shield the upper from direct contact with liquids

Dual density **ICON PU/PU** sole designed to offer maximum comfort, slip resistance, excellent performances across all terrains, from wet to dry conditions. It has been tested in SATRA laboratories to resist slipping on metal grates (Kennedy Grating Test) and wooden boards (Scaffold Board Test)



Dual density ICON PU/PU

- Resistant to hydrocarbons
- Antistatic sole (A)
- Non-slip sole suitable for use on metal and wooden grates - SATRA Tests
- Self-cleaning profile to ensure maximum ground grip
- Wide fit for maximum stability and protection
- Shock-absorbing heel

PZX fiberglass toe cap and **TXZERO STRONG** anti puncture insole made of high tenacity fibers to obtain a flexible textile that adapts to the movement of the foot; it is intrinsically antistatic



T-01

- Anatomical insole for increased comfort
- High-density foam = energy absorption and rebound
- Lining made from conductive micro-perforated fabric to reduce wear and tear



EXOTECH lining: non-woven fabric made from nylon fibres. It provides high sweat absorption, excellent foot breathability and high abrasion resistance

IDROTECH fullgrain leather upper, resistant to water penetration and absorption



A - Antistatic



PS - Anti-perforation insert



E - Energy absorption in the heel region



FO - Sole resistant to hydrocarbons



Toecap resistant up to an impact of 200 joules and crushing of 15 KN



SC - abrasion resistant overcap



WPA - Upper resistant to water penetration and absorption



LG - ladder grip system



SR - Slip resistance on ceramic tile with glycerin



Metal free

Esolight 1.0 polyurethane midsole. The low-density polyurethane microcells enhance energy absorption ensuring comfort and lightness